

# BRT26

Dual 6" + Tweeter 8 ohm  
Premium Install Speaker

## Key Features:

- ▶ Column Design
- ▶ Hi-Fi grade components
- ▶ Defined and accurate 120° x 40° dispersion
- ▶ Extended 77 Hz frequency response

## Applications:

- ▶ Performing Arts Facilities
- ▶ Houses of Worship
- ▶ Sports Facilities
- ▶ Multi Media Spaces
- ▶ Retail Spaces
- ▶ Presentation Suites
- ▶ Educational Facilities
- ▶ Portable Audio-Visual Systems

The BRT26 is a passive, compact trapezoidal, point-source cabinet ideally suited to background music, infill for portable and fixed installation use. The discreet design with articulated foam front and acrylic textured paint finish and multiple integrated fixing points achieves a high class look suitable for any application. The long rectangular shape of the BRT26 makes it ideal for mounting on Columns.

With a 120° x 40° horn loaded tweeter, the internal passive crossover ensures a flat, usable frequency response of 77 Hz to 26 kHz (-10 dB) and a maximum SPL of 120 dB (peak).

The discreet look makes them fit any style of décor. Using two custom 6" drivers and a horn loaded dome tweeter, creating a level of clarity and detail which is rare in a cabinet of this size.

Mounting options include integrated horizontal cradle fixing points and the rear pan and tilt bracket. Other fixings can be used with this cabinet such as the small wall bracket and pan and tilt pole mount adaptor.

The rear connector plate has two binding post connections & two 4 pin speakON® connectors fitted as standard, one input and one link. The speakON® connectors are wired on pins +1-1, with pass through of pins +2-2.

Custom colours are available on request to make their appearance even more seamless with the surroundings.



## Specifications

### Acoustic:

Design:	Mid-high cabinet, Reflex tuning
Frequency Response (+/-3 dB):	90 Hz - 24 kHz
Dispersion:	120° x 40°
System Sensitivity 2.83V / 1m:	93 dB
Max SPL:	114 dB cont / 120 dB peak
Impedance:	8 Ohm, minimum 6.7 @ 286 Hz
Max. Power Handling (AES):	500 Watts (program) / 1000 Watts (peak 10 ms)
Power Handling (AES):	250 Watts (continuous)
Components:	2 x 6" Low Frequency Driver, 1 x Horn loaded Tweeter
Connectors:	2 x 4 pole speakON® Connectors, 2 x Binding Post Connectors

### Aesthetic:

Crossover:	Passive - 3.5 kHz, Active - * LPF - / HPF - 110 Hz
Colour:	Black. White available upon request.
Dimensions (H x W x D):	460 x 190 x 188 mm
Weight:	6.6 kg
Rigging:	6 x M8 mounting points for installation brackets / cradle or truss adaptor

