

Models

TD-14000

Description

Few currently available SMPS amplifier platforms have achieved legendary status among the touring so quickly and unquestionably as our TD Series. The TD Series delivers superior sound quality, enduring severe stress, and keeping the show going on, no matter what.

In today's highly demanding touring environment, competitive sound hiring companies the world over have come to rely on DynaTech's TD Series amplifiers for performance that leads to profitability.



Specifications

Model	TD-14000
RMS Output Power (Per Channel, 8Ω)	2 × 2350 W
RMS Output Power (Per Channel, 4Ω)	2 × 4000 W
RMS Output Power (Per Channel, 2Ω)	2 × 7000 W
Rated Power (Bridge 8Ω)	1 × 8000 W
Rated Power (Bridge 4Ω)	1 × 1400 W
S/N Ratio (A Weight)	> 112 dB
Frequency Response (+0/-0.25dB)	20 Hz - 20 kHz
Class	D
Damping Factor	>1000 : 1
THD (10% Rated Power)	<0.05%
Input Connector	2 × XLR in, 2 × XLR Link Out
Input Impedance	10kΩ Unbalanced, 20kΩ Balanced
Output Connectors	Binding Post
Cooling	Two fans, Front to rear airflow, temperature controlled speed
Dimensions (H × W × D)(mm)	483 × 443 × 88
Net Weight (1 piece/pack)	13.5 Kgs
Gross Weight	16 Kgs