

XE-12

Passive Two-Way Speaker





Applications

- Portable Sound Reinforcement
- Foreground and Background Music Applications


Features


- 12 Inch woofer with paper cone for high sound quality
- True 1" compression driver for high system reliability and high intelligibility
- Angled Cabinet Design for Monitor Applications
- 'Top Hat' style stand adaptor for flexible mounting


The P.Audio XE-12 provides a cost effective background and foreground sound reinforcement solution to both portable and fixed install applications. The 12" woofer provides high intelligibility and extended low frequency response in a convenient, small profile design. The XE-12 is ideal for background music applications in pubs, bars, restaurants and retail outlets, as well as foreground full range music systems. The 1" true compression driver in the XE-12 features very high reliability, and is coupled to a 90 x 65 degree elliptical wave guide for controlled and detailed high frequency performance.


The passive network in XE-12 balances the output from both transducer components and provides optimal summing in the mid band region. The power handling is rated at 200 watts continuous with a peak input power of 800 watts.


Cabinet construction is of high quality wood with internal supports for extra rigidity, and is finished with high quality black paint. The XE-12 is a high performance design with superior vocal intelligibility from the high quality P.Audio components.











General Specifications

Туре	Passive Cabinet
Woofer Size	12"
Woofer Voice Coil	2.5"
HF Size	1"
HF Voice Coil	1"
Cabinet design	Plywood
Handles	2
Pole Mount	1 Top Hat Receptacle
Weight	14.2 kg / 31.3 lb
Dimensions (HxWxD)	550x346.5x362.7 mm / 21.7x13.6x14.3 in
A control of the cont	

Acoustic Specifications

Sensitivity (1w/1m)	93dB
-3dB Response	70Hz-18kHz
-10dB Response	60Hz-20kHz
Power Handling	200w Continuous (800w Peak)
Maximum Continuous SPL	116dB
Maximum Peak SPL	119dB
Dispersion (HxV)	90x65

Electrical Specifications

Impedance	8 Ohm
Input	Speakon
Thru	Speakon