XT-8 TWO WAY PASSIVE FULL RANGE



APPLICATIONS

- Very Compact Sound Reinforcement
- Fixed Install
- Portable Public Address

FEATURES

- 800 Watts Peak Power Handling (400 Watts Program,
 200 Watts Continuous)
- High Sensitivity
- 90 x 65 Acoustic Dispersion/Elliptic Wave Guide
- Very High Intelligibility
- Fully Optimized Linear Response

The P Audio XT-8 is a compact professional sound reinforcement system designed for foreground/background applications. The XT-8 is ideal for fixed installation applications such as restaurants, bars, retail outlets and general purpose indoor public address and full range music systems. The design of the XT-8 features a wide bandwidth 8 inch (203mm) low frequency device and a true compression driver coupled to an elliptical wave guide for controlled high frequency dispersion. The rated included angles are 90 degrees by 65 degrees.

The XT-8 is a full range design that employs a high order passive crossover that provides excellent summing and balance for the individual transducer components. The XT-8 features linear amplitude response, very defined intelligibility and superior reliability. The power handling is rated at 200 watts continuous with a peak input power capability of 800 watts. Maximum peak SPL is 122dB. System impedance is rated at 8 ohms.

The enclosure is constructed with high quality plywood and finished in a very durable polyurea coating. The system includes a top hat style stand adaptor and an optional "U" bracket to allow flexible mounting. The XT-8 is a very high performance design that features simple mounting for use in a variety of indoor applications.





XT-8 TWO WAY PASSIVE FULL RANGE




SPECIFICATIONS


Frequency Response (-10dB)	65Hz - 20kHz
Sensitivity (1w/1m)	92dB
Maximum Peak SPL	122dB
Dispersion(H x V)	90° x 65°
LF Components	8" Woofer
HF Components	1" Compression Driver
Input Impedance	8 Ohm
Connections	2 X Speakon Connectors
Power Handling	200w Continuous
	400w Program
	800w Peak
Net Weight	10 kg / 22 lbs
Dimensions (HxWxD)	429 x 246 x 275 (mm)
	16.9 x 9.7 x 10.8 (in)


OPTIONAL ACCESSORIES


- External "U" Bracket
- Standard 35 mm Pole mount to combine with subwoofer

DIMENSIONS













XT SERIES

SINCE 1991